

111-15419

Article Number: 111-15419

Description: Heavy-Duty Cable Tie, 32.3" Long, 175lb Tensile Strength, PA66, Natural, 25/pkg



Base Data	
Local Order Number	T150L9X2
Type	T150L
Color	Natural (NA)
Features and Benefits	<ul style="list-style-type: none"> • Heat stabilized heavy-duty cable ties provide excellent resistance to high heat exposures. • Head design provides high tensile strength with very low insertion force.
Quantity Per	bag
Product Description	HellermannTyton heavy duty cable ties offer a higher tensile strength for heavy load applications. The head design guarantees high tensile strength, as well as a low insertion force. For high-volume applications, tensioning tools are available to ensure consistent and safe installation.
Short Description	Heavy-Duty Cable Tie, 32.3" Long, 175lb Tensile Strength, PA66, Natural, 25/pkg
Product Dimensions	
Minimum Tensile Strength (Imperial)	175.0lbs
Minimum Tensile Strength (Metric)	780.0N
Length L (Imperial)	32.3"
Length L (Metric)	820.0mm
Fixation Method	None
Identification Plate Position	none
Releasable Closure	No
Tie Closure	plastic pawl
Variant	Inside Serrated
Width W (Imperial)	0.35"
Width W (Metric)	8.8mm
Bundle Diameter Min. (Imperial)	0.32"
Bundle Diameter Min. (Metric)	8.0mm
Bundle Diameter Max. (Imperial)	9.6"

111-15419



Product Dimensions	Bundle Diameter Max. (Metric)	245.0mm
	Thickness T (Imperial)	0.079"
	Thickness T (Metric)	2mm
Material and Specifications		
	Material	Polyamide 6.6 (PA66)
	Material Shortcut	PA66
	Flammability	UL 94 V2
	Halogenfree	Yes
	Operating Temperature	-40°F to +185°F (-40°C to +85°C)
	REACH Compliant (Article 33)	Yes
	ROHS Compliant	Yes
	Certification/Specification	UL ANSI/UL 746B
	UL Recognized (US and Canada)	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	25
	Package Quantity (Metric)	25Pieces
	Customs Number(Schedule B)	3926909987
	Content Unit (BMEcat)	pieces
	Weight (Metric)	16kg